

BARRACUDA

HIGH PRESSURE ROTARY NOZZLE

SURFACE PREPARATION

BARRACUDA

The Barracuda is a speed controlled rotary shotgun tool designed for speeds ranging from 1000 to 2000 rpm, making it ideal for cleaning thick, hard-to-remove materials like coke or rubber. The Barracuda can be used on automated and hands-free equipment.

- ✓ Handles a wide range of pressure ratings from 2–44k psi (140–3000 bar)
- ✓ Simple maintenance for long term use
- ✓ New cartridge seal doubles runtime
- ✓ Can be configured for 2 or 4 port application
- ✓ Angled jets allow for broader impact for quicker, more effective cleaning of large surfaces and odd shapes



TOOL MODEL	PRESSURE RANGE	FLOW RANGE	ROTATION SPEED	INLET CONNECTION	WEIGHT	MAX. WATER TEMP.
BC-K	2–22k psi (140–1500 bar)	4.4–13.3 gpm (17–50 l/min)	1000-2000 rpm	9/16" MP	2.7 lb (1.2 kg)	160 °F (70 °C)
BC-K-P2	5–22k psi (340–1500 bar)	4.3–12.1 gpm (16–46 l/min)	1000-2000 rpm	9/16" MP	2.7 lb (1.2 kg)	160 °F (70 °C)
BC-H9-C	20–44k psi (1400–3000 bar)	5.6–8.8 gpm (21-23 l/min)	1000-2000 rpm	9/16" HP	2.9 lb (1.3 kg)	160 °F (70 °C)
BC-H9LF-C	20–44k psi (1400–3000 bar)	4.3–6.7 gpm (16-25 l/min)	1000-2000 rpm	9/16" HP	2.9 lb (1.3 kg)	160 °F (70 °C)
BC-H9XLF-C	20–44k psi (1400–3000 bar)	3.5–5.6 gpm (13-21 l/min)	1000-2000 rpm	9/16" HP	2.9 lb (1.3 kg)	160 °F (70 °C)
BC-H9XXLF-C-TI	20–44k psi (1400–3000 bar)	2.3–3.8 gpm (9-14 l/min)	1000-2000 rpm	9/16" HP	3.2 lb (1.45 kg)	160 °F (70 °C)



BC 705 CARTRIDGE SEAL

Effectively doubles the life of the previous BC 505-S Cartridge Seal. For Barracuda rotary shotgun tools rated up to 44k psi (3000 bar).

NOZZLES AND PLUGS

Come in 2-port and 4-port configurations. Two jets deliver more concentrated power for heavy, thick deposits while four jets are ideal for removing thin, hard deposits.



IMPACT RESISTANT SHIELD

Inexpensive and easily replaceable shield protects working parts of the tool from debris and impacts.



**TOTAL
BLASTING**
water jetting technologies

