

# ORBIJET

## SURFACE CLEANING NOZZLE

MAINTAIN CONSISTENCY MAXIMIZE EFFICIENCY

**EASY TWO-MINUTE IN-THE-FIELD OVERHAUL**  
Using the Rebuild Kit with two standard hex wrenches

**MAGNETIC BRAKING SYSTEM**  
Controls rotational speed to reduce wear and maximize impact without streaking

**3 TOOLS IN 1**  
Two nozzles for a narrow path, two for a wide path (the widest in the industry), or all four nozzles for a complete clean

**TWIS-LOK™ LIGHTWEIGHT SHROUD**  
Protects tools and provides safe water displacement



INLET CONNECTION*	SPEED RANGE	DIAMETER (LESS SHROUD)		ASSEMBLY LENGTH (WITH ADAPTER)		ASSEMBLY WEIGHT		MAX. FLOW RATE (HAND GUN)		MAX. OPERATING PRESSURE**	
		RPM	IN	MM	IN	MM	LBS	KG	GPM	LPM	PSI
3/8" NPT Female	1000-1500	2.0	51	4.0	102	2.1	0.95	7.5	28.4	22,000	1517

\*Inlet connection on the tool is 9/16" MP; inlet listed is with the adapter.

\*\*With the 15K Adapter (not shown), Orbi-Jet X22 max pressure is 15,000 psi (1034 bar).



**TOTAL BLASTING**  
water jetting technologies

