



SAVING LIVES

HOSE PROTECTION 3000 BAR

The greatest risk areas of a hose break are near or on the water jet gun; areas often very close to the operator and near sensitive areas of the body, such as the abdomen, the arm pit or the neck. These are difficult areas to properly protect.

The Hose Protection, placed on the hose at the connection to the lance, protects the operator if a coupling or a hose breaks or if a pinhole leak occurs. In many countries, the use of hose protection is mandatory. And in some countries a whip stop is also required. Check the rules and regulations in your region.

We recommend at least 1400 mm/4.6 ft length. With this length, the operator has the best possible protection of the body. Also, the Hose Protection lies on the ground which means the operator doesn't have to carry the weight.



HOSE PROTECTION 3000 BAR

- Provides effective protection for the operator. Tested for 3 000 bar / 43 500 psi.
- An adjustable strap holds the Hose Protection to the lance.
- Metal ring at the bottom, a wear and tear protection for when the hose is on the ground.

HOSE PROTECTION Ø 36 MM			
LENGTH		ART. NO.	MOD. NO.
750 mm	2.5 ft	5060040	5920
1400 mm	4.6 ft	5060040	5940
1800 mm	5.9 ft	5060040	5960
HOSE PROTECTION Ø 38 MM PIPE EXTENSION 260MM			
1400 mm	4.6 ft	5060043	5940
HOSE PROTECTION Ø 47 MM SWIVEL			
1400 mm	4.6 ft	5060050	5942
HOSE PROTECTION Ø 47 MM PIPE EXTENSION 185 MM			
750 mm	2.5 ft	5060051	5920
HOSE PROTECTION Ø 59 MM			
750 mm	2.5 ft	5060060	5920
1400 mm	4.6 ft	5060060	5940
1800 mm	5.9 ft	5060060	5960

CE-certified PPE for water jetting, proven expertise, and a committed team, we make water jetting safer.



**TOTAL
BLASTING**
water jetting technologies



TST SAFETY